



The DRACONIS series from DEKO-LIGHT allows flexible ceiling lighting for a variety of applications in the areas of industry, trade and logistics. With the DRACONIS light for optional use as a surface-mounted ceiling light or in a 3-phase track system, the power [45, 55 or 72 W] and light colour [2,700, 3,500 or 4,000 K] can be flexibly adjusted using a switch on the back of the housing. To be able to integrate the DRACONIS into almost any environment, we offer several lenses for asymmetrical or symmetrical lighting in different light emission angles. The maximum luminous flux is 8,215 lumens.

#### Special features

- Power adjustable in 3 stages
- Light colour adjustable in 3 stages
- High luminous flux

<b>Housing Material</b>	Die-cast aluminium	<b>Life Time L70 / B50</b>	50000 h
<b>Housing Color</b>	Aluminum	<b>Switching Cycles</b>	25000
<b>Protection Class</b>	Protection class I/protective grounding	<b>Power Consumption</b>	72 kWh/1000h
<b>Power Selectable</b>	45 W, 55 W, 72 W	<b>Energy Efficiency Class</b>	E
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Dimmable</b>	No		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Lightcolor</b>	Neutral white/warm white		
<b>Color Temperature</b>	2700/3500/4000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	8215 lm		
<b>Luminous Efficiency</b>	114.1 lm/W		
<b>Rated Angle of Reflection</b>	60 Degree		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Below		
<b>Length</b>	577.6 mm		
<b>Width</b>	188.6 mm		
<b>Height</b>	128.7 mm		
<b>Product weight</b>	2634 g		
<b>Working Temperature</b>	-20 to 30 °C		
<b>Storage Temperature</b>	-30 to 60 °C		
<b>IP Protection Class</b>	IP 20		