

Han 34HPR Hood



Image is for illustration purposes only. Please refer to product description.

Part number	09 40 134 0601
Specification	Han 34HPR Hood
HARTING eCatalogue	https://b2b.harting.com/09401340601

Identification

Category	Accessories
Series of hoods/housings	Han [®] HPR EasyCon
Type of hood/housing	Protection cover
Description of hood/housing	for carrier hoods

Version

Size	34 HPR
Locking type	Screw locking

Technical characteristics

Tightening torque	6 Nm Protection cover
	6 Nm Fixing screws
Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP65
	IP68
	IP69 / IPX9K acc. to ISO 20653

Material properties

Material (hood/housing)	Aluminium die-cast
	Corrosion resistant
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
RoHS	compliant with exemption



Pushing Performance
Since 1945

Material properties

RoHS exemptions	6(a) / 6(a)-I: Lead as an alloying element in steel for machining purposes and in galvanised steel containing up to 0,35 % lead by weight / Lead as an alloying element in steel for machining purposes containing up to 0,35 % lead by weight and in batch hot dip galvanised steel components containing up to 0,2 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R1 (HL 1-3) R7 (HL 1-3)

Commercial data

Packaging size	1
Net weight	1,629 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140192126
eCl@ss	27440208 Cap for industrial connectors