

## Panel mounting socket outlet, angled - flange 100x92, fixing centers 85x77



| Product description       |  |
|---------------------------|--|
| BALS-Prd.-Nr              | 12832  |
| EAN                       | 4024941128322                                      |
| Product category          | Panel mounting socket outlet Quick-Connect, angled |
| Current                   | 16A  |
| Number of poles           | 4p   |
| Poles                     | 3P+PE  |
| Position of earth contact | 9 h  |
| Voltage                   | 200 up to 250V                                     |

| Product description            |   |
|--------------------------------|---|
| Frequency                      | 50 and 60Hz   |
| Protection degree              | IP67  |
| Colour code                    | blue RAL 5015   |
| Colour of appliance            | Hinged lid blue RAL 5015, Bayonet ring grey RAL 7035, Enclosure grey RAL 7035 |
| Connection design              | screwless spring terminals as cage clamp with Kontex-contact                  |
| Maximum conductor size         | 4,0 qmm   |
| Cable entry                    | other   |
| Height                         | 100mm   |
| Width                          | 92mm  |
| Depth                          | 98mm  |
| Flange size vertical           | 100mm   |
| Flange size horizontal         | 92mm  |
| Drill hole distance vertical   | 85mm  |
| Drill hole distance horizontal | 77mm  |
| Material of enclosure          | Polyamide   |
| Contact                        | The contact carrier is made of polyamide, The contacts are brass              |

| Additional technical properties |                        |
|---------------------------------|------------------------|
|                                 | The inclination is 20° |

| Logistics data |                |
|----------------|----------------|
| Weight/pcs     | 0.0 kg / Piece |
| Packaging      | Bag            |
| Content amount | 1 ST           |
| EAN            | 4024941128322  |
| Length         | 98 mm          |
| Width          | 92 mm          |
| Height         | 100 mm         |
| Weight         | 0.001 kg       |
| Volume         | 901.6 ccm      |
| Packaging      | Carton         |
| Content amount | 10 ST          |
| EAN            | 4024941830560  |
| Length         | 245 mm         |
| Width          | 177 mm         |
| Height         | 185 mm         |
| Weight         | 0.133 kg       |
| Volume         | 7,140 ccm      |



4 MB 115

| Ampere                     | 16   | 16    | 16    | 32    | 32    | 32    |
|----------------------------|------|-------|-------|-------|-------|-------|
| Polzahl                    | 3    | 4     | 5     | 3     | 4     | 5     |
| a                          | 74,0 | 100,0 | 100,0 | 100,0 | 100,0 | 100,0 |
| b                          | 62,0 | 92,0  | 92,0  | 92,0  | 92,0  | 92,0  |
| c                          | 60,0 | 85,0  | 85,0  | 85,0  | 85,0  | 85,0  |
| d                          | 52,0 | 77,0  | 77,0  | 77,0  | 77,0  | 77,0  |
| e ø                        | 5,5  | 5,5   | 5,5   | 5,5   | 5,5   | 5,5   |
| f                          | 8,0  | 8,0   | 8,0   | 8,0   | 8,0   | 8,0   |
| h                          | 46,0 | 46,0  | 46,0  | 55,0  | 55,0  | 55,0  |
| i                          | 57,0 | 57,0  | 60,0  | 65,0  | 65,0  | 69,0  |
| k                          | 57,0 | 65,0  | 70,0  | 75,0  | 75,0  | 78,0  |
| l                          | 52,0 | 65,0  | 70,0  | 75,0  | 75,0  | 78,0  |
| α                          | 20°  | 20°   | 20°   | 20°   | 20°   | 20°   |
| Leiter mm <sup>2</sup> min | 1,5  | 1,5   | 1,5   | 2,5   | 2,5   | 2,5   |
| Leiter mm <sup>2</sup> max | 4    | 4     | 4     | 10    | 10    | 10    |