




The pendant lamps of the new MEROPE series combine timeless elegance and subdued modernity. Available in the diameters 400, 600 and 800 mm, the light colour [3,000/4,000 K] can be selected before installation using a CCT switch. The outside is finished in brushed aluminium in the colours white, silver, coffee and black.

Special features

- High luminous flux
- Light colour adjustable in 2 stages
- Suspended mounting up to 1,800 mm

Housing Material	Aluminium	Storage Temperature	-10 to 45 °C
Housing Color	Silver	IP Protection Class	IP 20
Housing Surface	Brushed	Life Time L70 / B50	30000 h
Material of Lens	Acryl	Switching Cycles	20000
Protection Class	Protection class I/protective grounding	Power Consumption	42 kWh/1000h
Rated Input	42 W	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	Yes		
Control technology	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	3000/4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	3100/3200 lm		
Rated Luminous Flux 2	3200 lm		
Light Distribution	Symmetric		
Light Exit Surfaces	1		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		
Height	60 mm		
Diameter	580 mm		
Base height	65 mm		
Base diameter	220 mm		
Pendulum Length max.	1800 mm		
Working Temperature	-10 to 45 °C		