


QualityFlex COB-Vision RGBW LED-Flexplatine 50 mm, CRI > 90, 16

W / m, IP00

Article no. 75507002

Light.
For Generations.



Tender

RGBW LED-Flexplatine 50 mm, CRI > 90, 16 W / m, IP00, white, CRI > 90. LED flex lighting for Länge: 50.0 mm Lampenleistung je Meter: 16.0 W/m, Schutzart raumseitig: IP00, Schutzklasse: III, Spannung: 24V, Abstrahlwinkel: 120.0 °, 560 LEDs pro Meter. Zur Individuellen Anwendung kann die LED-Flexplatine alle 50 mm eingekürzt werden. Die maximale Systemlänge von 5.000mm darf mit einer Einspeisung nicht überschritten werden.

Product Benefits

- Effektvolles Farbspiel und Weißlicht in einer LED-Flexplatine.
- RGBW Chip-on-Board LED Bestückung für homogenes Lichtbild.
- Variantenreiche Beleuchtung von Lichtvouten, Linearanwendungen und Lichtdecken.
- Lichtfarben: rot / grün / blau / weiß.
- Zahllose Mischfarben umsetzbar.
- Geeignet für Anwendungen im Innenbereich (IP00).
- Kompatibel mit unseren 4 Kanal 24 V DC-Steuerungen, RGBW.

QualityFlex COB-Vision RGBW LED-Flexplatine 50 mm, CRI > 90, 16**W / m, IP00**

Article no. 75507002

Light.
For Generations.

Article data	
Article no.	75507002
Series name	QualityFlex COB-Vision
Short description	RGBW LED-Flexplatine 50 mm, CRI > 90, 16 W / m, IP00
Colour	White
Length	50 mm
Width	12 mm
Height	2 mm
Scope of delivery	inkl. 1 x Montageanleitung
Weight	0.000 kg
Length of the connection line	500 mm

Lighting technology	
Colour temperature	RGBW
Light colour	RGBW
Farbtemperatur 1	3,000 K
Lichtstrom 1	324 lm
Lichtstrom rot	136 lm
Lichtstrom grün	292 lm
Lichtstrom blau	80 lm
System efficiency	16 lm/W
McAdam-Step	McAdam-Step 3
Colour rendering	CRI > 90
Beam angle	120°

Operating technology of the luminaire	
Lamp power per meter	16 W/m
Voltage type	DC
DC nominal voltage max	24 V
Lamp	LED
Protection class	III
Degree of protection	IP00
Ambient temperature	-10 °C bis +40 °C
Dimmable	Yes
Wire number	5
Control	Dimming depending on driver
Length of the connection line	500 mm
Kabelbelegung	schwarz = + weiß = - weiß blau = - blau grün = - grün rot = - rot
Design of the connecting cable	einseitig
Bulb change possible	No
Rated life time L70/B50 at 25 °C	52000 h
Energieeffizienzklasse	F

Operating technology of QualityFlex	
Number of lamps per meter	560 Qty
Length of individual sections	50 mm
Smallest bend radius	20 mm
Length	50 mm
Maximum module length	5,000 mm
Circuit type	Parallel conduction
LED Type	COB-LED

QualityFlex COB-Vision RGBW LED-Flexplatine 50 mm, CRI > 90, 16**W / m, IP00**

Article no. 75507002

Light.
For Generations.

Packing data	
Gross weight	0 kg
Length of packaging	210 mm
Packaging width	200 mm
Packaging height	20 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

Compatible Driver						
Article no.	Power min	Power	Control	Length	Width	Height
17206000	1 W	20 W	1-10 V	146 mm	55 mm	19 mm
17207000	1 W	30 W	on/off	160 mm	50 mm	22 mm
17214000	1 W	7.2 W	on/off	68 mm	35 mm	21 mm
17223000	1 W	75 W	on/off	185 mm	60 mm	31 mm
17224000	1 W	100 W	on/off	199 mm	63 mm	36 mm
17225000	1 W	150 W	on/off	219 mm	63 mm	36 mm
17226000	1 W	240 W	on/off	244 mm	71 mm	38 mm
17240000			on/off			

Compatible Controller						
Article no.	Power min	Power	Control	Length	Width	Height
18151000	24 W	240 W	KNX	170 mm	59 mm	30 mm
18152000	24 W	240 W	DALI	170 mm	59 mm	30 mm
18153000	24 W	240 W	DMX	170 mm	59 mm	30 mm
18154000	24 W	240 W	1-10 V	170 mm	59 mm	30 mm
18161000	24 W	240 W	KNX	72 mm	90 mm	70 mm
18162000	24 W	240 W	DALI	54 mm	110 mm	66 mm
18164000	24 W	240 W	1-10 V	54 mm	110 mm	66 mm
18223000	0 W	240 W	Wireless technology control			
18157000	48 W	240 W	Zigbee	145 mm	46.5 mm	16 mm
18192000	120 W	240 W	Wireless technology control	160 mm	45 mm	18 mm

Compatible Profiles				
Short description	Series name	Length	Width	Height
Surface-mounted profile	P04-14	2,000 mm	24 mm	9 mm
Surface-mounted profile	P06-20	2,000 mm	23 mm	25.1 mm
Surface-mounted profile	P16-16	2,000 mm	18.8 mm	18.6 mm
Surface-mounted profile, high	QualityFlex ONE		17.6 mm	15.9 mm
Recessed profile	P34-14	2,000 mm	28 mm	8 mm
Recessed profile	P36-20	2,000 mm	30 mm	20.4 mm
Plaster profile	P37-30	2,000 mm	63.4 mm	15.9 mm
Plaster profile	P38-30	2,000 mm	63.4 mm	24 mm
Wall recessed profile	P32-12	2,000 mm	19.1 mm	81 mm
Surface-mounted corner profile	P62-14	2,000 mm	24 mm	19.4 mm
Surface-mounted corner profile	P63-14	2,000 mm	17.5 mm	17.5 mm
Surface-mounted corner profile	QualityFlex ONE		24 mm	19.4 mm
Wall surface-mounted profile	P73-12	2,000 mm	17.8 mm	46.1 mm
Wall surface-mounted profile	P74-14	2,000 mm	18.5 mm	55 mm
Ceiling recessed profile with wall mounting	P75-14	2,000 mm	28 mm	28 mm