


# lightnet


## Matric-A3

Surface mounted light-line - Direct light distribution

Article code: LA3ABL-830H-L2055



Illustrations may only be similar and serve as an orientation.



Matric-A3. LED. Wall or ceiling mounted light-line. Luminaire body made of high-quality aluminum profile. Surface finish Jet Black. Direct only light distribution. Colour temperature: 3000(Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. Dimmable DALI. LxWxH (rectangular). L=2055mm. W=55mm. H=75mm. High-power


current. 5133lm. 54W. 5,2kg. Binning initial  $\leq$  MacAdam 3. IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

# lightnet

## Matric-A3

Surface mounted light-line - Direct light distribution

Article code: LA3ABL-830H-L2055



Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

|                              |                                |
|------------------------------|--------------------------------|
| Productname                  | Matric-A3                      |
| Lamp                         | LED                            |
| Installation Type            | Surface mounted light-line     |
| Surface finish               | Jet Black                      |
| Light characteristics        | Direct light distribution      |
| Colour temperature           | 3000K                          |
| Colour Rendering Index (CRI) | CRI>80                         |
| Optical system               | Microprismatic screen          |
| Control                      | Dimmable (DALI)                |
| Length L/Diameter D (mm)     | L=2055mm                       |
| Width W (mm)                 | W=55mm                         |
| Height H (mm)                | H=75mm                         |
| Current/Power                | High-Power                     |
| Luminous Flux                | 5133lm                         |
| Power consumption            | 54W                            |
| Degree of protection         | IP20                           |
| Certification                | Prüfzeichen: ENEC              |
| LED lifetime                 | L80B10 (tq 25°C) = 50.000h     |
| Photometric code             | 8 30 / 3 3 9                   |
| Photobiological class        | RG0 (EN62471)                  |
| Indoor/Outdoor               | Indoor: ta [ambient] max. 25°C |
| Weight (kg)                  | 5,2kg                          |

