



The UNI II series includes high-quality surface-mounted lamps for use on walls and ceilings in commercial and private spaces. The rotatable and swivelling lamp heads have warm white COB LEDs and if required can be folded flush to the mount to shine vertically downwards like a ceiling spotlight. In addition to the single, double and triple designs, there is both a mini version (with smaller lamp head and mount) and a MAX version available. There is also a variant for use in current tracks.

Special features

- High colour rendering
- Can be rotated and swivelled
- Dimmable

Housing Material	Die-cast aluminium, Steel, Polycarbonate	IP Protection Class	IP 20
Housing Color	White	Life Time L70 / B50	50000 h
Material of Lens	Polycarbonate - PC	Life Time L80 / B10	50000 h
Protection Class	Protection class I/protective grounding	Switching Cycles	50000
Rated Input	21 W	Power Consumption	21 kWh/1000h
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class F.
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	Yes		
Control technology	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	2700 K		
Colour Consistency	3 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	1360 lm		
Rated Angle of Reflection	36 Degree		
Swivel Angle	90 Degree		
Rotation Angle	350 Degree		
Light Exit Surfaces	2		
Light characteristics	Direct		
Light direction	Below		
Length	160 mm		
Width	75 mm		
Height	91 mm		
Working Temperature	-10 to 55 °C		
Storage Temperature	-20 to 60 °C		